

# SIGHT MARK®



## Ultra Shot M-Spec FMS (Fixed Mount-Standard)

### SPECIFICATIONS

Reticle type	65 MOA Circle Dot Crosshair (60 MOA circle w/ 5 MOA subextension, 2 MOA central dot)
Reticle color	red
Illuminated reticle (yes/no)	yes
Brightness settings	off, 1-8, NV1- NV6
Magnification (x)	1
Window dimension (mm)	33x24
Window material	glass
Field of view (m @100m)	35
Field of view (ft @100yd)	105
Eye relief (mm)	unlimited
Elevation adjustment MOA	120
Windage adjustment MOA	120
MOA adjustment (one click)	1
Finish/color	matte black
Body material	magnesium alloy
Maximum recoil (caliber)	up to .50cal
IP Rating (waterproof)	IP68 - submersible to 40ft
Shockproof (yes/no)	yes
Fog proof (yes/no)	no
Lens coatings	AR red
Mount type	weaver/picatinny
Battery type	CR2
Battery life (hours)	90 - 1000
Battery voltage (V)	3
Operating temp (°F)	-20 to 140
Dimensions (mm)	103 x 49 x 61
Weight (oz)	7.5

### FEATURES

- ✦ Fixed mount design fits weaver/picatinny rails
- ✦ Advanced, true color anti-reflective lens coating improves low light and night vision performance
- ✦ Motion sensing auto-on feature
- ✦ Cast magnesium alloy housing with protective shield
- ✦ IP68 Waterproof rating - submersible to 40ft
- ✦ Low power consumption
- ✦ Digital switch controls
- ✦ Variable reticle brightness with night vision modes
- ✦ Interlok™ internal locking system
- ✦ Scratchproof lenses
- ✦ Lightweight
- ✦ Shockproof (.50cal)
- ✦ Wide field of view
- ✦ Parallax corrected
- ✦ Unlimited eye relief

### INCLUDED

- ✦ Neoprene cover
- ✦ Adjustment tools
- ✦ Battery
- ✦ Manual

Featuring a digital switch control with eight variable brightness levels for daytime use and six settings in night vision mode, the Sightmark® Ultra Shot™ M-Spec FMS Reflex Sight is built for quickly adapting to any shooting environment.